

READ FITTING INSTRUCTIONS IN FULL BEFORE INSTALLATION

This article is sold without warranty expressed or implied. No warranty or representation is made as to this product's ability to protect the user from injury or death. The user assumes that risk. The effectiveness, warranty and longevity of this equipment are directly related to the manner in which it is INSTALLED, USED, and/or MAINTAINED. THE USER ASSUMES THE RISK.

By purchasing this product and opening the packaging, purchasers expressly acknowledge, understand and agree that they take, select and purchase these SECTOR 111 products from SECTOR 111, its affiliates, distributors, and agents (collectively, SECTOR 111) "as is" and "with all faults".

The entire risk as to the quality and performance of these SECTOR 111 parts is with the purchasers. Working on your car can be a dangerous activity. If you are unsure of what you are doing, please leave mechanical or Safety critical work to a skilled mechanic.

We take no responsibility for the incorrect use and/or installation of SECTOR 111 products.

microMIRROR™ Installation Directions

Do not try to remove your stock mirror if the ambient temperature is below 60deg F. Be careful and gentle through this entire process as you can crack your windshield. If you have any concerns with removing your stock mirror, please have your dealer or a professional do the work.

1. Remove stock rear view mirror (we recommend you recruit a friend to help). See figure 1.
 - a. The cover at the base of the stock mirror pivots down at the top.
 - i. Pull this cover down to expose the retainer clip
 - b. Release the retainer clip with a very small flat screwdriver (or paint can opener, see figure 2) and slide the mirror down towards the dash at the same angle as the windshield
 - i. Take care to protect the windshield when leveraging with the screwdriver



Figure 1.



Figure 2.

2. Assemble the microMIRROR.
 - a. Apply red Loctite to threads of the Mirror
 - b. Screw it into the Post
 - c. Use a ¼" wrench to tighten the Mirror Body to the Post
3. Install microMIRROR to windshield
 - a. Slide the post base up into the stock windshield cleat
 - b. Center the post
 - i. You can choose to position it higher or lower.
 - c. Tighten set screws in the base of the Post with a 2mm allen wrench
4. Adjust microMIRROR. Enjoy the improved forward visibility!
5. Contact us at info@sector111.com or 951-296-6762 with any questions