Mobil 1 Engine Oils

Additional product information, including Product Data Sheets and this chart, is available at Mobiloil.com 10/17/2011

			Nominal Zinc Level,			API, ILSAC, and Other Industry			Ford Service Fill	МВ	BMW	vw
		Nominal		,								
		Phosphorus			Recommended		ACEA	GM Service				
Brand	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
				Boosted, advanced full synthetic								
				formula designed for today's								
Mobil 1				longer oil change intervals in								
Extended				Honda, Chryslers and newer	Vehicles that require 5W-		A1/B1-08					
Performance	5W-20	800	900	Toyotas	20	GF-5,SN	A1/B1-10		Х			
				Boosted, advanced full synthetic								
Mahila				formula designed for today's			A1/B1-08,					
Mobil 1				longer oil change intervals in			A5/B5-08,					
Extended	EW 20	000	000	many domestic, including GM,	Vehicles that require 5W-		A1/B1-10,	deveed	v			
Performance	5W-30	800	900	and imported vehicles.	30 or 10W-30.	Honda HTO-06	A5/B5-10	dexos1	Х			
				Department, and some and fault as well as the			A4/D4 00					
Mahild				Boosted, advanced full synthetic			A1/B1-08,					
Mobil 1				formula designed for today's			A5/B5-08,					
Extended	1014/ 20	000	000	longer oil change intervals in	Vehicles that require 5W-		A1/B1-10,					
Performance	10W-30	800	900	many domestics and imports.	30 or 10W-30.	GF-5,SN	A5/B5-10					
	014/ 20				Most vehicles that							
	0W-20			Advanced full synthetic	specify 0W-20 (newer							
	Advanced			formulation designed for	Toyotas and Hondas),		A1/B1-08.					
Mahild	Fuel	050	750	enhanced fuel economy and cold	5W-20 and certain		,		v			
Mobil 1	Economy	650	750	weather performance.	hybrids.	GF-5,SN	A1/B1-10		Х			
	0W-30			Advanced full synthetic								
	Advanced			formulation designed for	Most vehicles that							
M-1-11-4	Fuel	050	750	enhanced fuel economy and cold			A1/B1-10,		X			
Mobil 1	Economy	650	750	weather performance.	30.	GF-5,SN	A5/B5-10		Х			
				Advanced full synthetic		Chrysler						
				formulation designed to meet the	Porsche A40.	MS10850,						
M-1-11-4	014/ 40	4000	1100	requirements of many European	Many European vehicles.	Nissan GT-R	A3/B3-08,			229.3/		502.00 /
Mobil 1	0W-40	1000	1100	vehicles.	HT/HS applications.	SN,SM,SL,SJ	A3/B4-08			229.5	Longlife 01	505.00
				Advanced full synthetic								
				formulation designed to meet the								
				requirements of many newer								
				vehicles including Hondas,								
				Fords, Chryslers and newer	Vehicles that require 5W-		A1/B1-08,					
Mobil 1	5W-20	800	900	Toyotas.	20.	GF-5,SN	A1/B1-10,		Х			
				Advanced full synthetic								
				formulation designed to meet the			A1/B1-08,					
				requirements of many domestic,			A5/B5-08,					
				including GM, and imported	Vehicles that require 5W-	GF-5,SN	A1/B1-10,					
Mobil 1	5W-30	800	900	vehicles.	30. Corvette approved.	Honda HTO-06	A5/B5-10	dexos1	Х			
				Higher viscosity, advanced full								
	5144 50			synthetic formula designed for	Porsche.	01/01/	A3/B3-08,			229.1		501.01,
Mobil 1	5W-50	1000	1100	performance vehicles	HT/HS applications.	SN/SM	A3/B4-08			/229.3		505.00
							A1/B1-08,					
				Advanced full synthetic formula			A5/B5-08,					
				designed for domestics and	Vehicles that require 5W-		A1/B1-10,					
Mobil 1	10W-30	800	900	imports	30 or 10W-30.	GF-5,SN	A5/B5-10					\
				Boosted, higher viscosity,								
				advanced full synthetic formula	HT/HS applications.		A3/B3-08,					
				designed for performance	Racing and Flat tappet		A3/B4-08,					
Mobil 1	15W-50	1200	1300	vehicles.	applications.	SN/SM	A3/B3-10					
				Advanced full synthetic formula	Most diesel applications.	CJ-4, CI-4,						
Mobil 1 Turbo				designed for diesel powered pick-		CI-4 Plus, SM,						
Diesel Truck	5W-40	1100	1200	ups and trucks.	diesel particulate filters.	SL	E7					

		Nominal	Nominal			API, ILSAC, and Other		· · · · ·	Ford Service			
		Phosphorus	Zinc Level,		Recommended	Industry	ACEA	GM Service	Fill	МВ	BMW	vw
Brand	Viscosity	Level, PPM	PPM	Product Description	Consumer Applications	Approvals***	Approvals	Fill Approval	Approval	Approval	Approval	Approval
2.4.14	lieccelly				eeneunie Appneunene		A1/B1-08.			, appi e rai	, pp. e rai	, pp. et al
				Boosted, advanced full synthetic			A5/B5-10,					
Mobil 1 High				formula designed for higher	Vehicles that require 5W-		A1/B1-10,					
Mileage	5W-30	1000	1100	mileage vehicles.	30 or 10W-30.	SL/SJ	A5/B5-10					
				Boosted, advanced full synthetic			A3/B3-08,					
Mobil 1 High				formula designed for higher	Vehicles that require 5W-		A3/B4-08,					
Mileage	10W-30	1000	1100	mileage vehicles.	30 or 10W-30.	SL/SJ	A3/B3-10					
				Boosted, advanced full synthetic			A3/B3-08,					
Mobil 1 High				formula designed for higher	Higher viscosity		A3/B4-08,					
Mileage	10W-40	1000	1100	mileage vehicles.	applications.	SN/SM/SL/SJ	A3/B3-10					
				Advanced full synthetic formulas								
				designed specifically for	Low SAPS.							
Mobil 1 ESP				passenger car diesels that have	Available at most MB					229.31,		
Formula M	5W-40	800	900	particulate filters.	dealers.	None				229.51		
				Advanced full synthetic formulas		D 1 000						
Mobil 1 ESP				designed specifically for	Low SAPS.	Porsche C30.				000.04		
Formula	5W-30	000	000	passenger car diesels that have particulate filters.	Available at many	Chrysler MS- 11106	C2 00 C2 00			229.31, 229.51		504/507
Formula	500-30	800	900	particulate filters.	Chrysler dealers.	11106	C3-08, C2-08			229.51	Longlife-04	504/507
				Advanced full synthetic formulas								
				designed specifically for		SN/SM/SJ/SH.						
Mobil 1 Racing				motorcycles where clutch	All motorcycles where	JASO MA1						
4T	10W-40	1200	1300	lubrication is also important.	10W-40 is specified	2006						
	1011 10	1200	1000			2000						
				Advanced full synthetic formulas	All motorcycles where							
				designed specifically for	20W-50 is specified,							
				motorcycles where clutch	especially V-Twin							
Mobil 1 V-Twin	20W-50	1600	1700	lubrication is also important.	engines	SJ						
				Advanced full synthetic formula								
			1	specifically designed to maximize	Race engines. Not							
			1	horsepower under race	recommended for street							
Mobil 1 Racing	0W-30	1750	1850	conditions.	use.							
				Advanced full synthetic formula								
			1	specifically designed to maximize	Race engines. Not							
			1	engine protection under race	recommended for street							
Mobil 1 Racing	0W-50	1750	1850	conditions.	use.							

** API SH and API SG are no longer licensable. ***For a full list of industry and original equipment manufacturer approvals by product and viscosity, see the Product Data Sheets which are available online at www.mobiloil.com.